Type 2 AC EV Charger

MODEL:
RHAC7K-XC | RHAC11K-XC | RHAC21K-XC



Consolidated Metal shell for more Durability

IP54 Protection

Comprehensive electrical safety protections

Compatible with all type 2 vehicles

4G/WiFi access for advanced software functions

Highly heat and humidity resistant

www.9sunsolar.com / www.9sunsolar.net

Type 2 AC EV Charger
Parameter list

Specifications	Model	RHAC7K-XC	RHAC11K-XC	RHAC21K-XC
Input	Power Supply	1P+N+PE	3P+N+PE	3P+N+PE
	Rated Voltage	230V±15%	400V±15%	400V±15%
	Rated Current	32A	3*16A	3*32A
	Frequency	50/60 Hz	50/60 Hz	50/60 Hz
Output	Output Voltage	230V±15%	400V±15%	400V±15%
	Maximum Current	32A	3*16A	3*32A
	Rate Power	7kW	11kW	22kW
User Interface	Charge Connector	Type 2 cable		
	Cable Length	5 m		
	LED Indicator	Green/blue/Red		
	LCD Display	4.3 inch LCD		
	RFID Reader	MifareISO/IEC14443A		
	Starting Methods	Plug&Play/RFID card/App		
	Emergency Stop	Yes		
Network Connection	LAN	Yes		
	4G	optional		
	Wifi	Yes		
	Bluetooth	Yes		
	OCPP	OCPP 1.6 J		
Safety Measures	Energy Meter	Yes		
	RCD	6mA DC		
	Ingress Protection	IP54		
	Impact Protection	Ik10		
	Electrical Protections	Over current protection Residual current protection Surge protection Over/Under voltage protection Over/Under Frequency protection Over temperature protection		
	Certification	CE/CB		
	Certification Standards	EN IEC 61851-1:2019, IEC 61851-1:2017, EN 61851-21-2:2018		
	Warranty	2 Years		
Operating Conditions	Installation	Wall-mount/Pole-mount (Optional)		
	Operating Temperature	-30°C~+50°C		
	Humidity	5%~95%		
	Altitude	<2000m		
Packaging	Product Dimension	350*250*122 mm (H*W*D)		
	Package Dimension	550*350*220 mm (L*W*H)		
	Net Weight	6.5 kg	7.5kg	9.5kg
	Gross Weight	7.5kg	8.5kg	10.5kg
	Others	Carton		